17

CLAIM AMENDMENTS

- (currently amended) A railroad box car comprising: 1 a truck-carrying railroad chassis; a horizontal floor on the chassis; a horizontal roof above the floor; a pair of upright and transverse end walls between the roof and floor; a pair of upright and longitudinal side walls between the end walls, roof and floor, the side and end walls on the chassis forming with the roof and floor a closable longitudinally extending space, the side and end walls each being formed of an inner skin, 10 an outer skin, and a mass of cellular plastic foam between the 11 skins bonded at least to an outer face of the respective inner 12 skin, at least one of the side walls being formed by a two longitu-13 dinally slidable doors together extending substantially a full longitudinal length of the space and movable into open positions 15 giving open transverse access to the entire space; and
 - 2. (canceled)
- 3. (currently amended) The railroad box car defined in claim [[2]] 1 wherein each outer [[wall]] skin is spaced from the respective inner [[wall]] skin.

means for conditioning air in the space.

4. (canceled)

- 5. (currently amended) The railroad box car defined in claim [[4]] 1 wherein the doors have lower edges provided with rollers and the box car further comprises longitudinally extending tracks on which the rollers ride.
- 6. (original) The railroad box car defined in claim 5 wherein the tracks are carried on the chassis below the floor.
- 7. (original) The railroad box car defined in claim 6 wherein the doors extend downward past the floor.
- 8. (currently amended) The railroad box car defined in claim [[4]] 1 wherein the doors have upper edges and the roof has tracks in which the upper edges slide.
- 9. (original) The railroad box car defined in claim 8
 wherein the door upper edges have inwardly angled extensions
 sliding on the tracks.

- 3 -

- 10. (original) The railroad box car defined in claim 4,
- 2 further comprising
- latch means for arresting the doors relative to the roof
- and floor.

11. (canceled)

- 12. (original) The railroad box car defined in claim 2 wherein the roof is formed by a longitudinally extending roof beam.
- 13. (original) The railroad box car defined in claim 12 wherein the roof beam is cambered.
- 14. (original) The railroad box car defined in claim 13
 wherein the roof beam is shaped so as to urge the doors into closed
 positions.
- 15. (original) The railroad box car defined in claim 12 wherein the roof beam is formed with air-flow passages connected to the conditioning means.

16. (canceled)

17

18

19

20

17. (original) The railroad box car defined in claim 4, 1 2 further comprising seals on the end walls, roof, and floor engaging edges of the doors in closed positions thereof. (new) A railroad box car comprising: 1 a truck-carrying railroad chassis; a longitudinally extending horizontal floor on the chassis; a longitudinally extending horizontal roof above the floor and of a transverse width substantially less than the floor; a pair of upright and transverse end walls between the roof and floor; a pair of upright and longitudinal side walls between the end walls, roof and floor, the side and end walls forming with the 10 roof and floor a closable longitudinally extending space, the side 11 and end walls each being formed of an inner skin, an outer skin, 12 13 and a mass of cellular plastic foam between the skins bonded at least to an outer face of the respective inner skin, at least one 14 of the side walls being formed by a pair of longitudinally extend-15 ing openable doors each having 16

a vertical lower portion,

on the floor,

a lower edge on the lower portion and slidable

an inwardly angled upper portion, and

21	an upper edge on the upper portion slidable on
22	the roof, whereby when open the doors give
23	full-height transverse access to the
24	space; and
25	means for conditioning air in the space.